

DECLARATION OF PERFORMANCE

BB-Roof 130

- Unique identification code of the product-type:
Roof 130
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):
Roof 130 (stated on packaging or printing of the product)
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Application: Flexible sheets for water proofing – Part 1: Underlays for discontinuous roofing EN 13859-1
Application: Flexible sheets for water proofing – Part 2: Underlays for walls EN 13859-2
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Baltijos Brasta Ltd., Palemono str. 7B, LT-52158 Kaunas
- Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not listed
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
system 4
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
not applicable
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not applicable
- Declared performance:
Harmonised technical specification EN 13859-1:2010; EN 13859-2:2010

Property	Essential characteristics		Performance		
	Method	Units	Nominal	Minimum	Maximum
Water vapour transmission (sd)	EN 12572	m	0,05	-20%	+20%
Water tightness	EN 13859	Class	W1	-	-
Reaction to fire	EN 11925-2	Class	F	-	-
Maximum tensile force (MD)	EN 12311-1	N/50mm	292	-20	+20
Elongation at max. Tensile force (MD)	EN 12311-1	%	77	-25	+25
Maximum tensile force (CMD)	EN 12311-1	N/50mm	178	-15	+15
Elongation at max. Tensile force (CMD)	EN 12311-1	%	70	-15	+15
Resistance to tearing MD (nail shank)	EN 12310-1	N	120	-20	+20
Resistance to tearing CMD (nail shank)	EN 12310-1	N	150	-20	+20
Flexibility at low temperature	EN 1109	°C	-20	-	-
Artificial ageing by UV and heat:	EN 13859	Change			
Water tightness		Class	W1	-	-
Maximum tensile force (MD)		%	<30	-	-
Elongation at max. Tensile force (MD)		%	<35	-	-
Maximum tensile force (CMD)		%	<30	-	-
Elongation at max. Tensile force (CMD)		%	<35	-	-
Additional properties					
Mass per unit area	EN 1849	g/m ²	130	-10%	+10%
Length	EN 1848	m	50	-0,5%	+0,5%
Width	EN 1848	m	1,5	-0,5%	+0,5%

MD – machine dimension; CMD – cross machine dimension.

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Kaunas, 2013-07-01
Project manager

Saulius Pupius




UAB „Baltijos Brasta”

Palemono g.7B, LT-52158 Kaunas • Tel. +370 37 457021, faksas +370 37 453732
el. paštas: info@baltijosbrasta.lt • www.baltijosbrasta.lt
Įmonės kodas 177304814 • PVM mokėtojo kodas LT773048113
A/s LT94 7044 0600 0310 3958, AB „SEB Vilniaus bankas”, banko kodas 70440