

DECLARATION OF PERFORMANCE

BB-Silver Anticon

1. Unique identification code of the product-type:
Silver Anticon
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):
Silver Anticon (stated on packaging or printing of the product)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Application: Flexible sheets for water proofing – Part 1: Underlays for discontinuous roofing EN 13859-1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Baltijos Brasta Ltd., Palemono str. 7B, LT-52158 Kaunas
5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not listed
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
system 4
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
not applicable
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not applicable
9. Declared performance:
Harmonised technical specification EN 13859-1:2010

Property	Essential characteristics		Performance		
	Method	Units	Nominal	Minimum	Maximum
Reaction to fire	EN 13501	Class	F	-	-
Water tightness	EN 1928	Class	W1	-	-
Maximum tensile force (MD)	EN 12311-1	N/50mm	400	-30	+30
Elongation at max. Tensile force (MD)	EN 12311-1	%	13	-5	+10
Maximum tensile force (CMD)	EN 12311-1	N/50mm	350	-35	+35
Elongation at max. Tensile force (CMD)	EN 12311-1	%	14	-5	+10
Resistance to tearing MD (nail shank)	EN 12310-1	N	300	-20	+20
Resistance to tearing CMD (nail shank)	EN 12310-1	N	270	-20	+20
Flexibility at low temperature	EN 1109	°C	-20	-	-
Artificial ageing by UV and heat:	EN 13859	Change			
Water tightness		Class	W1	-	-
Maximum tensile force (MD)		%	<30	-	-
Elongation at max. Tensile force (MD)		%	<30	-	-
Maximum tensile force (CMD)		%	<30	-	-
Elongation at max. Tensile force (CMD)		%	<30	-	-
Additional properties					
Mass per unit area	EN 1849	g/m ²	110	-10%	+10%
Length	EN 1848	m	40	-0,5%	+0,5%
Width	EN 1848	m	1,5	-0,5%	+0,5%

MD – machine dimension; CMD – cross machine dimension.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Kaunas, 2013-07-01
Project manager

Saulius Pupius


